ACT1-LED-B

ACT D'MAND Kontrols[®] Systems



SUBMITTAL DATA	
JOB/CUSTOMER:	SUBMITTED BY:
ENGINEER:	APPROVED BY:
CONTRACTOR:	ORDER NO:
SPECIFICATION REFERENCE:	
	OPTIONAL ACCESSORIES Hardwired LED Button Hardwired Rocker Switch Hardwired Motion Sensor Bluetooth Wireless Transmitter Kit Bluetooth Wireless Motion Sensor Bluetooth Repeater Under Sink Mounting Kit (For Systems w/o Return Lines) UDES es with: s Steel Unions (1) Hardwired LED Button
(1) ACT1 Pump (1) Integrated Check Valve (1) Integrated Temperature Sensor	
FLOW RANGE: 0-15 GPM	MAX. WORKING PRESSURE: 145 PSI
HEAD RANGE: 0-24 Ft.	CONNECTORS: 1" BSP Union x ¾" MIP
MOTORS: 2-POLE SINGLE PHASE	RPM/HP: 3450 RPM/.17HP
MIN. FLUID TEMPERATURE: 36°F MAX. FLUID TEMPERATURE: 150°F	VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.2LBS
DIMENSIONS	PERFORMANCE CHART
00 00 00 00 00 00 00 00 00 00 00 00 00	0 0 2 4 6 8 10 12 14 16 GPM

PHONE: (800) 200-1956

www.GotHotWater.com

FAX: (714) 668-1927