SS3-200-PFS | ACT D'MAND Kontrols® Systems



SUBMITTAL DATA	
JOB/CUSTOMER:	SUBMITTED BY:
ENGINEER:	APPROVED BY:
CONTRACTOR:	ORDER NO:
SPECIFICATION REFERENCE:	



INCLUDES


The Original D'MAND KONTROLS® System Standard package comes with:


- (1) 3-Speed Control Box with Power Cord, Activation Wires
- (1) SS3-200 Pump

- (1) Integrated Check Valve
- (1) Integrated Temperature Sensor
- (1) Hardwired Activation Button
- (2) Flanges with Bolts and Nuts
- (2) Stainless Steel Tees
- (2) 18" Flex Lines
- (1) Large Mounting Bracket

TECHNICAL DATA	
FLOW RANGE: 0-33 GPM	MAX. WORKING PRESSURE: 145 PSI
HEAD RANGE: 0-29 Ft.	CONNECTORS: GF 15/26 Flange (With ¾" Stainless Steel MIP not shown in picture)
MOTORS: 2-POLE SINGLE PHASE	RPM/HP: 3450/.262hp
MIN. FLUID TEMPERATURE: 36°F	VOLTAGE (max. spd.): 115V/197 watts/1.80 Amps
MAX. FLUID TEMPERATURE: 230°F	APPROX SHIP WEIGHT: 17 LBS

DIMENSIONS





PERFORMANCE CHART

