ACT2-BTR

ACT D'MAND Kontrols[®] Systems



SUBMITTAL DATA	
JOB/CUSTOMER:	SUBMITTED BY:
ENGINEER:	APPROVED BY:
CONTRACTOR:	ORDER NO:
SPECIFICATION REFERENCE:	



- ☐ Hardwired LED Button
- ☐ Hardwired LED Rocker Switch
- ☐ Hardwired Motion Sensor
- ☐ Bluetooth Wireless Transmitter
- ☐ Bluetooth Wireless Motion Sensor
- ☐ Bluetooth Repeater

PROGRAMMABLE DIGITAL CONTROLLER

INCLUDES

The Original D'MAND Kontrols® System Standard Package Comes with:

- (1) Control Box ACT2 w/ power cord, activation wires (1) Small Mounting Bracket
- (1) ACT1 Pump
- (1) Integrated Bluetooth Activation
- (1) Integrated Check Valve
- (1) Integrated Temperature Sensor

- (2) Blue POM Tees ½" x ½" x ¾"
- (2) 1/2" x 3/8" x 12" Flex Lines
- (2) 1/2" FPT x 3/8" Male Comp Adapters
- (1) Anchor Pack

TECHNICAL DATA	
FLOW RANGE: 0-15 GPM	MAX. WORKING PRESSURE: 145 PSI
HEAD RANGE: 0-24 Ft.	CONNECTORS: 1" BSP Union x ¾" MIP
MOTORS: 2-POLE SINGLE PHASE	RPM/HP: 3450 RPM/.17HP
MIN. FLUID TEMPERATURE: 36°F	VOLTAGE (max. spd.): 115V/125 watts/1 Amp
MAX. FLUID TEMPERATURE: 150°F	APPROX SHIP WEIGHT: 10 LBS

DIMENSIONS

