ACT D'MAND Kontrols[®] Systems ACT2



	SUBMITTAL DATA
JOB/CUSTOMER:	SUBMITTED BY:
ENGINEER:	APPROVED BY:
CONTRACTOR:	ORDER NO:
SPECIFICATION REFERENCE:	
	OPTIONAL ACCESSORIES
	□ Hardwired LED Button
POWER ON-	ACT Hardwired LED Rocker Switch
PUMPON ●	Handwired Motion Sensor
	Bluetooth Wireless Transmitter
	Bluetooth Wireless Motion Sensor
	Bluetooth Repeater
PROGRAMMABLE DIGITAL C	ONTROLLER Under Sink Mounting Kit (For Systems w/o Return Lines)
	INCLUDES
The Original D'MAND Kontrols® Syste	
(1) ACT1 Pump	tivation wires (1) Integrated Temperature Senso (2) Stainless Steel Unions
(1) Integrated Bluetooth Activation	
	(1) Hardwired LED Button
(1) Integrated Check Valve	(1) Hardwired LED Button (1) Anchor Pack
(1) Integrated Check Valve	
(1) Integrated Check Valve	(1) Anchor Pack
(1) Integrated Check Valve TEC	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1"
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft.	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN.	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F DIMENSIONS	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F DIMENSIONS	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F DIMENSIONS	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART
(1) Integrated Check Valve TEC FLOW RANGE: 0-15 GPM HEAD RANGE: 0-24 Ft. MOTORS: 2-POLE SINGLE PHASE MIN. MIN. FLUID TEMPERATURE: 36°F MAX FLUID TEMPERATURE: 150°F DIMENSIONS	(1) Anchor Pack CHNICAL DATA MAX. WORKING PRESSURE: 145 PSI CONNECTORS: 1" BSP Union x ¾" MIP RPM/HP: 3450 RPM/.17HP VOLTAGE (max. spd.): 115V/125 watts/1 Amp APPROX SHIP WEIGHT: 8.5 LBS PERFORMANCE CHART